

TAKISAWA TWIN CHUCKER

TT-Series

Parallel Twin-Spindle CNC Lathe

6in/8in

TT-2100



TT-2100G TT-2100CMG

TAKISAWA®

TT-2100G

Mass production of various workpieces with high accuracy!

Takisawa twin chucker **TT-2100G** is a parallel twin-spindle lathe which is equipped with high speed gantry loader and supports mass production with high accuracy in 6"/8" chuck work.

Flexibly Supporting Any Type of Production

Takisawa twin chucker TT-series supports any type of production such as simultaneous front & back machining, symmetrical machining, and full automatic machining by connecting machines/creating production line, and provides excellent efficiency and high productivity.



ENERGY SAVING SYSTEM

- Reduction of power consumption.
 - Regenerative energy system – the energy generated when the motor decelerates returns to the power supply – is applied.
 - Internal lighting shutoff function reduces standby power.
 - Control panel cooling design takes natural radiation amount into account to reduce electric power.
 - Coolant pump runs only when coolant is being used, reducing electric power.
- Use of oil-water separator extends the coolant life.
- 40% reduction of lubricant consumption amount compared with those of conventional machines.
- The powder coating machine for environmental concern.

Environment Friendly



*The photo includes options (Foot Switch for Hydraulic Chuck, Turning Tools).


Bed

The bed has a tank bed structure which can keep thermal displacement to the minimum all day.
Tank capacity = 350L



Sliding Surface

Wide rectangular slideways are used in the X-/Z-axes sliding surfaces to realize stable machining with high accuracy over a long period of time.



Headstock

Both of stable cutting and high speed loader transfer are achieved by adopting a structure of low center of gravity in which the center height of the headstock from the floor surface kept low.

There are two types of specifications for high accuracy spindle on the headstock: "6" chuck specification" and "8" chuck specification", which are combined with FANUC's high performance spindle motors to provide excellent performance.


Movable partition covers are provided at the center between the two spindles to secure safety and workability.




6" Chuck Type

7.5/5.5kW FANUC: β i16

4500min⁻¹ Standard




6000min⁻¹




11/7.5kW FANUC: β i18

4500min⁻¹




6000min⁻¹




8" Chuck Type

11/7.5kW FANUC: β i18

3200min⁻¹ Standard



4500min⁻¹



6" Chuck Type

Spindle Stock and Spindle Motor

Bearing Inside Diameter	ϕ 80
Spindle Nose	ϕ 140F
Spindle Motor	7.5/5.5kW
Spindle Speed	4500min ⁻¹
Spindle Motor	11/7.5kW
Spindle Speed	4500min ⁻¹
Spindle Motor	6000min ⁻¹
Spindle Speed	6000min ⁻¹

Standard Chuck and Cylinder

Chuck Type	H01MA6
Travel of Jaw (Diameter)	7mm
Max. Speed	4500min ⁻¹
Cylinder Type	HH9C100
Max. Speed	6500min ⁻¹

8" Chuck Type

Spindle Stock and Spindle Motor

Bearing Inside Diameter	ϕ 90
Spindle Nose	ϕ 140F
Spindle Motor	11/7.5kW
Spindle Speed	3200min ⁻¹
Spindle Motor	4500min ⁻¹
Spindle Speed	4500min ⁻¹

Standard Chuck and Cylinder

Chuck Type	H01MA8
Travel of Jaw (Diameter)	7mm
Max. Speed	4000min ⁻¹
Cylinder Type	HH9C125
Max. Speed	6000min ⁻¹

Red is Optional.


Turret

The turret is the all-holder powerful type with bolt clamping system.

10-station turret (T10) is equipped as standard, and 12-station turret (T12) for multiple processes and 10-station milling turret (T10M) for milling processes are optionally available.

In a 10-station milling turret (T10M), milling holders can be equipped to five stations (every second station).


Items	Items	Items	6" Chuck Type	8" Chuck Type
10-Station Turret	T10 (Standard)	Height of Square Tool Shank	\square 20	\square 25
		Diameter of Boring Bar Shank	ϕ 25	ϕ 32
12-Station Turret	T12 (Optional)	Height of Square Tool Shank	\square 20	\square 25
		Diameter of Boring Bar Shank	ϕ 25	ϕ 32
10-Station Turret	T10M (Optional)	Height of Square Tool Shank	\square 20	\square 25
		Diameter of Boring Bar Shank	ϕ 25	ϕ 32
		Max. Rotary Tool Shank Diameter	ϕ 16	ϕ 16



Milling Type

5.5/3.7kW FANUC: β i13

2500min⁻¹




Gantry Loader

The machine's center of gravity is thoroughly lowered and the loader axis is improved to move faster and quieter to realize optimum cycle time.

Loader Cycle Time **19.6 sec**
(6"Chuck Type, A Type Gantry)

Gantry Loader Variations



Loader Specification (A or B Type)

Items	6" Chuck Type	8" Chuck Type
Target Workpiece	Outside Diameter	ϕ 80mm
	Length	80mm
	Weight	0.7kg (\times 2)
Running Speed	X-Axis (Longitudinal)	200m/min
	Y-Axis (Vertical)	150m/min

Work Feeder Specifications

Items	6" Chuck Type	8" Chuck Type
Number of Pallets	16	16
Loading Capacity (1 Pallet)	40kg	40kg
Maximum Height	450mm	450mm

Reversing Device

The device allows simultaneous front and back machining.

* Unlike connecting two one-spindle lathes with a reversing device provided between them, even the space efficiency is obvious.



Pursuing Operability



• Dedicated Switch

A dedicated switch to call a desired function to the operation panel with one push is provided for smooth work.



2 Program Reset Function

Left/right/loader programs can be reset and rewind.

3 Zero Point Return Function

It allows left/right X- and Z-axes zero point return and loader X-, Y-, and Z-axes zero point return.*

*) Subject to some conditions. For details, contact us.

Function to minimize inputting error on right and left.

4 Right/Left Selection Button

Operate the machine after selecting right or left with the button. Operation is possible only on the side with the indication lamp turned on. When both of the lamps are turned off, the machine cannot be operated.



Operation on Right Side ▶

The information on the right side is displayed on the screen and you can operate the right side.

Link of Panel Light ▶

The light on the operation side is turned on.



5 Chuck Open/Close Switch



6 Machine Operation Panel Screen

The machine operation panel is displayed on the screen. Buttons can be added and displayed/undisplayed easily.

7 Information Display Window


"Right/left selection, indexed turret number of right/left machine, and number of workpieces on right/left" can be checked in the upper right of the screen.

• Information on Right and Left is Displayed Simultaneously (Specific Screen)


On the tool offset screen and the workpiece shift screens, inputting errors are avoided by color coding of right/left, the zoom function and simultaneous display.

In addition, software pursuing operability is provided as standard to reduce non-productive time during setup work.

In addition, software pursuing operability is provided as standard to reduce non-productive time during setup work. Refer to page 13.





▲ Program Display





▲ Tool Offset Display

Tooling System




T10/T12 6" Chuck Type Turning Type TT-2100G


Ranges depends on chuck type.



T10 TURRET (R) is mirror-image component. Figure shows TURRET (L).





T12 TURRET (R) is mirror-image component. Figure shows TURRET (L).




T10/T12 8" Chuck Type Turning Type TT-2100G


Ranges depends on chuck type.





T10 TURRET (R) is mirror-image component. Figure shows TURRET (L).





T12 TURRET (R) is mirror-image component. Figure shows TURRET (L).



T10M 6" Chuck Type Milling Type TT-2100CMG Ranges depends on chuck type.



T10M 8" Chuck Type Milling Type TT-2100CMG Ranges depends on chuck type.



Machine Specifications (with A or B Type Loader)

Items	6" Chuck Type			8" Chuck Type		
	TT-2100G	TT-2100CMG		TT-2100G	TT-2100CMG	
Capability - Capacity	Distance Between Spindles	mm	340	340	340	340
	Max. Turning Diameter	mm	240	240	240	240
	Max. Turning Length	mm	135.5	135.5	94	94
Travel	X-Axis Travel	mm	142	142	142	142
	Z-Axis Travel	mm	165	165	165	165
Spindle	Number of Spindles		2	2	2	2
	Spindle Speed	min ⁻¹	4500	6000	3200	4500
	Min. Index Angle (Cs-Axis)	deg	-	0.001	-	0.001
	Spindle Nose (Nominal Code)		φ 140F	φ 140F	φ 140F	φ 140F
	Through-Hole Diameter	mm	53	53	53	53
Turret	Bearing Inside Diameter	mm	80	80	90	90
	Number of Turrets		2	2	2	2
	Type of Turret (All-Holder Type)		10-Station	12-Station	10-Station	10-Station
Rotary Tool	Number of Attachable Tools		10+10	12+12	10+10	10+10
	Height of Square Tool Shank	mm	20	20	25	25
	Diameter of Boring Bar Shank	mm	25	25	32	32
Feedrate	Number of Rotary Tools		-	Alternate 5 pcs	-	Alternate 5 pcs
	Spindle Speed	min ⁻¹	-	2500	-	2500
	Maximum Tool Shank Diameter	mm	-	16	-	16
	Tool Spindle Taper Hole (Type, Nom. Code)		-	AR25	-	AR25
	Tool Spindle Bearing Inside Diameter	mm	-	35	-	35
Motor	Rapid Traverse Rate	m/min	X:24 / Z:24	X:944.88" / Z:944.88"	X:24 / Z:24	X:944.88" / Z:944.88"
	Jog Feedrate	mm/min	X:24 / Z:24	X:944.88" / Z:944.88"	X:24 / Z:24	X:944.88" / Z:944.88"
Required Power	Main Spindle Motor (15 min/continuous) *6	kW	7.5/5.5	11/7.5	10/7.3	14.7/10
	Rotary Tool Spindle Motor (15 min/continuous)	kW	-	5.5/3.7	-	5.5/3.7
	Feed Axis Motor	kW	X:1.4 / Z:1.4	X:1.9 / Z:1.9	X:1.4 / Z:1.4	X:1.9 / Z:1.9
	Hydraulic Pump Motor	kW	1.5x2 Motors	2x2 Motors	1.5x2 Motors	2x2 Motors
	Coolant Pump Motor	kW	0.25x2 Motors	0.3x2 Motors	0.25x2 Motors	0.3x2 Motors
Tank Capacity	Electric Power	kVA	32	37	37	37
	Air Pressure Source	MPa	0.4	0.4	0.4	0.4
	Hydraulic Unit Tank	L	20 (x2)	5.28 (x2)	20 (x2)	5.28 (x2)
Machine Size	Lubricant Tank	L	6.5	1.72	6.5	1.72
	Coolant Tank	L	350	92.40	350	92.40
	Machine Height	mm	2700	106.30"	2700	106.30"
Machine Size	Floor to Spindle Center Height	mm	975	38.39"	975	38.39"
	Required Floor Space	mm x mm	2825 x 2627	111.22" x 103.43"	2825 x 2627	111.22" x 103.43"
	Machine Weight	kg	5200	11440	5400	11880

Loader Specifications (A or B Type)

Target Workpiece	6" Chuck Type			8" Chuck Type		
	TT-2100G	TT-2100CMG		TT-2100G	TT-2100CMG	
Outside Diameter	mm	80	3.15"	160	6.3"	80
Length	mm	80	3.15"	80	3.15"	80
Weight	kg	0.7x2	1.5x2	3x2	6.6x2	3x2
Travel (Running Speed)	X-Axis (longitudinal)	mm/min	1540	60.63"	200	7874.02"
	Y-Axis (vertical)	mm/min	662	26.06"	150	5905.51"
	Z-Axis (cross)	mm/min	216	8.5"	50	1968.5"
Hand	Type		3-Jaws	3-Jaws	3-Jaws	3-Jaws
	Stroke	mm	φ 28	1.1"	φ 32	1.25"

Work Feeder Specifications

Number of Pallets		16	16
Loading Capacity (1 Pallet)	kg	40	88
Max. Height	mm	450	17.72"

Red is Optional. [*1] or [*2] are options by a set.

Machine Standard Accessories (with A or B Type Loader)

Items	Contents	6" Type	8" Type
Solid Chuck and Cylinder	H01MA8 & HH9C125	L&R	×
	H01MA6 & HH9C100	L&R	×
Chuck Open/Close M-Function	(Proximity)	L&R	●
Chuck Airblow	(Outside Spindle)	L&R	●
Signal Tower Light	(3-Color)	1 Pic	●
Chip Conveyor	(Caterpillar Type, Rear)	1 Set	●
Tool Holders	(Selectable for OD Turning & Facing, or Boring Bar/Drill)	L&R (Each 5)	●
Auto Power-Off System		1 Set	●
Total Counter	(Display)	●	●
Gantry Loader *3	(A or B Type)	1 Set	●
Turnover Unit		1 Set	●
NG Chute	(Quality)	1 Set	●
Work Feeder	(16 Pallets/3 Guide Bar)	1 Set	●
Splashguard		1 Set	●
Hydraulic Unit	(1.5kW)	L&R	●
Coolant Unit	(250W)	L&R	●
Lighting Apparatus		1 Set	●
Adjustment Tool		1 Set	●
Instruction Manual		1 Set	●


Machine Optional Accessories

- Rotary Tool Holder (for X-Axis) *4
- Rotary Tool Holder (for Z-Axis) *4
- Collet (for Rotary Tool) *4
- Tool Holder
- Boring Bar / Drill Holder
- Offset Boring Bar Holder
- U-Drill Holder
- Offset U-Drill Holder
- Boring Bar Bush
- Drill and U-Drill Socket
- Special Chuck
- Foot Switch for Hydraulic Chuck
- Spindle Orientation *5
- Coolant Unit (400W)
- Spindle Above Coolant
- Hybrid Hydraulic Unit
- Chip Bucket
- Tool Setter
- Spindle Motor

*3) Includes Safety Cover/Upper Auto Door/Door Interlock.
 *4) Applied to TT-2100CMG
 *5) Disk Brake Type (Max. 360 Point) with M-Function
 *6) Please refer to "Electric-power-equipment Capacity" of 13 page.

※ For other optional accessories, please contact us.

Machine Dimensions Unit : mm inch



TT-2100G

NC Unit Specifications

FANUC : Oi-TF
 ※ Please contact our sales persons for further information.




Software

* The software specifications are subject to change for improvement without notice.

RAKU-RAKU Loader 4


[Standard Accessory]
 The loader operation settings can be changed simply by the operation from the dedicated screen without modifying the program.



▲ RAKU-RAKU Loader 4

RAKU-RAKU Monitor 3

[Standard Accessory]
 Easy and convenient multi-functional softwares which can perform tool life management, cutting load monitoring, group control, and also run information collection, Cp (process capability) calculation, and periodic offset addition.



▲ RAKU-RAKU Monitor 3

Measurement Monitor 3

[Optional Accessory]

This function loads the measured data from a measuring unit and sets automatically the offset value. Also, various convenient functions such as graphical display, Cp (process capability) calculation, and data input/output are included.

Electric-power-equipment Capacity

Spindle Motor	Gantry (Type)	6" Chuck Type		8" Chuck Type	
		TT-2100G, TT-2100CMG			
5.5/7.5kW	A, B, C	32.0kVA	32.0kVA	32.0kVA	32.0kVA
	D	33.0kVA	33.0kVA	33.0kVA	33.0kVA
7.5/11kW	A, B, C	37.0kVA	37.0kVA	37.0kVA	37.0kVA
	D	38.0kVA	38.0kVA	38.0kVA	38.0kVA

Composition

Specifications · Contents	TT-2100G	TT-2100CMG
[NC Unit]		
Screen (10.4" Color LCD/MDI (Horizontal, Small Type))	●	●
[Software]		
RAKU-RAKU Loader 4	●	●
RAKU-RAKU Monitor 3	●	●
Measurement Monitor 3 *1	◎	◎
[Safety Devices]		
Front Door Interlock	●	●
Front Door Locking Mechanism	○	○
Safety Relay	●	●
Control Panel Breaker with Tripper	●	●

Main Function List

Specifications · Contents	TT-2100G
[Controlled Axes]	
Least Input Increment *2	●
Max. Programmable Dimension (±999999.999)	●
Cs Contouring Control	CM
Increment System C *3	▲
Inch/Metric Conversion	●
Interlock	●
Machine Lock *4	○
Emergency Stop	●
Stored Stroke Check 1	●
Stored Stroke Check 2, 3 *5	▲
Stored Limit Check Before Move	▲
Chuck and Tail Stock Barrier *6	▲
Mirror Image (Each Axis)	▲
Chamfering ON/OFF	●
Unexpected Disturbance Torque Detection Function *7	●
Position Switch	●
[Operation]	
Automatic Operation (Memory)	●
MDI Operation	●
DNC Operation *8 *9	○
DNC Operation with Memory Card *9 *10	○
Program Number Search	●
Sequence Number Search	●
Sequence Number Comparison and Stop	●
Program Restart	◎
Tool Retract and Recover	▲
Wrong Operation Prevention	▲
Buffer Register	●
Dry Run	●
Single Block	●
Manual Continuous Feed (JOG)	●
Manual Reference Position Return	●
Reference Position Setting without DOG	●
Manual Handle Feed, 1 Unit	●
[Interpolation Functions]	
Positioning (G00)	●
Exact Stop Mode (G61)	●
Tapping Mode (G63)	●
Cutting Mode (G64)	●
Exact Stop (G09)	●
Linear Interpolation (G01)	●
Circular Interpolation (G02/G03)	●
Dwell (G04)	●
Polar Coordinate Interpolation	CM
Cylindrical Interpolation	CM
Thread Cutting, Synchronous Cutting	●
Multi Threading	●
Thread Cutting Retract	●
Continuous Threading	●
Variable Lead Thread Cutting	●
Skip (G31)	◎
Reference Position Return (G28)	●
Reference Position return Check (G27)	●
2nd Reference Position Return (G30)	●
3rd, 4th Reference Position Return	◎

Specifications · Contents	TT-2100G
[Feed Functions]	
Rapid Traverse Override (F0,25%,50%,100%)	●
Feed Per Minute	●
Feed Per Revolution	●
Constant Tangential Speed Control	●
Cutting Feedrate Clamp	●
Automatic Acceleration/Deceleration	●
Rapid Traverse Bell-Shaped Acceleration/Deceleration	●
Linear Acceleration/Deceleration After Cutting Feed Interpolation	●
Feedrate Override (15 Steps)	●
Jog Override (15 Steps)	●
Override Cancel	●
Manual per Revolution Feed	▲
[Program Input]	
Program Code (EIA/ISO Auto Recognition)	●
Label Skip	●
Parity Check	●
Control In/Out	●
Optional Block Skip, 1 Piece	●
Optional Block Skip (2 to 9 Pieces)	◎
Program Number 04 Digits	●
Program File Name 32 Characters	●
Sequence Number N8 Digits	●
Absolute/Incremental Programming	●
Decimal Point Programming/Pocket Calculator Type Decimal Point Programming	●
Diameter/Radius Programming (X-Axis)	●
Plane Selection G17,G18,G19	CM
Coordinate System Setting (G50)	●
Automatic Coordinate System Setting *11	●
Workpiece Coordinate System(G54-G59) *12	▲
Direct Drawing Dimension Programming *13	▲
G-Code System A	●
G-Code System B/C	▲
Chamfering/Corner R *14	●
Programmable Data Input (G10)	●
Sub Program Call (10 Levels)	●
Custom Macro	●
Additional Custom Macro Common Variables	●
Canned Cycle	●
Multiple Repetitive Cycles	●
Multiple Repetitive Cycles II	●
Canned Cycle for Drilling	●
Circular Dnterpolation by R Programming	●
Coordinate System Shift	●
Direct Input of Coordinate System Shift	●
[Auxiliary / Spindle Speed Function]	
M Function (M3 Digits)	●
2nd Auxiliary Function (B Function)	●
Multiple Command of Auxiliary Function (3 Pieces)	●
Spindle Speed Function (S-Function)	●
Constant Surface Speed Control	●
Spindle Override	●
Spindle Orientation	●
Rigid Tap (Spindle Center)	●
Rigid Tap (Rotary Tool)	CM
[Tool Functions / Tool Compensation]	
Tool Function (T2+2 Digits)	●
Tool Offset Pairs 128-pairs (L/R Each 64-pairs)	●
Tool Offset Pairs 200-pairs (L/R Each 99-pairs)	○
Tool Offset	●
Tool Radius · Tool Nose Radius Compensation	●
Tool Geometry/Wear Compensation	●
Tool Offset Value Counter Input	●
Direct Input of Tool Offset Value Measured	●
Direct Input of Tool Offset Value Measured B *15	○
Tool Life Management *16	●
[Accuracy Offset Functions]	
Backlash Compensation	▲
Backlash Compensation for Each Rapid Traverse and Cutting Feed	▲
[Editing]	
Part Program Storage Size 1Mbyte *17	●
Part Program Storage Size 2Mbyte *17	○

Specifications · Contents	TT-2100G
Number of Registerable Programs, 800 Programs *18	●
Number of Registerable Programs, 1000 Programs *18	○
Part Program Editing	●
Extended Part Program Editing	●
Program Protect	●
Playback	◎
Machining Time Stamp	○
Background Editing	●
Multi Part Program Editing	●
[Setting / Display]	
Status Display	●
Clock Function	●
Current Position Display	●
Program Comment Display (31 Characters)	●
Parameter Setting and Display	●
Alarm Display	●
Alarm Log Display	●
Operation History Display	▲
Run Hours and Parts Count Display	●
Actual Cutting Feedrate Display	●
Display of Spindle Speed and T Code at All Screens	●
Servo Setting Screen	●
Maintenance Information Screen	●
Data Protection Key, 1 Kind	●
Erase CRT Screen Display	●
Parameter Set Supporting Screen	●
Help Function	●
Self-diagnosis Function	●
Periodic Maintenance Screen	●
[Multi-language Display]	
English *19	●
Other Language *19 *20	▲
Dynamic Display Language Switching	▲
[Data I/O]	
RS-232C Interface for 1ch	○
Data Server Function *21	◎
External Workpiece Number Search	◎
Memory Card I/O	●
USB Memory I/O	●
One Touch Macro Call	◎
Automatic Data Backup	●
[Communication Function]	
Embedded Ethernet	●
Fast Ethernet	◎
[Other]	
Touch Panel	◎

● : Standard ○ : Optional ◎ : Special — : None
 ▲ : Parameter setting is required.

(Note: Normally, the parameters need not to be changed. If the parameters are to be set or changed, understand completely the functions of such parameters. Wrong setting could cause the machine to be moved unexpectedly, resulting in machine or workpiece damage or personal injury.)

CM : C-Axis/Milling Standard Specification.

- *1) I/O addition and the PC change are necessary.
- *2) 0.001mm, 0.0001inch, 0.001deg
- *3) IS-C 0.0001mm, 0.0001deg, 0.00001inch.
- *4) Addition of switch is required.
- *5) Not coexistent with chuck tailstock barrier.
- *6) Not coexistent with Stored Stroke Check 2, 3.
- *7) Required when RAKU-RAKU Monitor 3 is used.
- *8) RS-232C Interface is required.
- *9) DNC run mode transfer switch is required.
- *10) CF card and adaptor is required.
- *11) Not coexistent with Workpiece Coordinate System(G54-G59).
- *12) Not coexistent with Automatic Coordinate System Setting.
- *13) Not coexistent with chamfering/corner R.
- *14) Not coexistent with direct drawing dimension programming.
- *15) Tool setter is required.
- *16) Cannot be used when RAKU-RAKU Monitor 3 is installed.
- *17) In the case of loader specification, about [262K-byte 655m] is used for program store capacity by RAKU-RAKU loader 4 software.
- *18) In the case of loader specification, the 180 program number is used by RAKU-RAKU loader 4 software.
- *19) Cannot be simultaneously displayed with other languages.
- *20) Japanese, German, French, Spanish, Italian, Chinese (traditional), Chinese (simplified), Korean, Portuguese, Dutch, Danish, Swedish, Hungarian, Czech, Polish, Russian, Turkish, Romanian, Bulgarian, Slovak, Finnish
- *21) Optional board is required.

TT-2100G

TAKISAWA®

TAKISAWA MACHINE TOOL CO., LTD.

983 Natsukawa, Kita-ku, Okayama 701-0164, JAPAN

Telephone : (81)86-293-1500

Fax : (81)86-293-5799

Website : <http://www.takisawa.co.jp>

E-mail : tkj-1@takisawa.co.jp (America)

tkj-2@takisawa.co.jp (Europe)

tkj-3@takisawa.co.jp (Asia)

Japanese laws prohibit this machine from being used to develop or manufacture "weapons of mass destruction" or "conventional arms", as well as from being used to process parts for them.

Export of the product may require the permission of governmental authorities of the country from where the product is exported.

Should you wish to resell, transfer or export the product, please notify Takisawa Machine Tool Co., Ltd. or our distributor in advance.

*The appearance, specifications, and relevant software of the product are subject to change for improvement without notice.

*Please make an inquiry to our sales representatives for details of the product.



ISO 9001 Certified
JQA-2010
(Head Office)



ISO 14001
12ER-865
(Head Office)

Overseas Network

- THAILAND** Takisawa (Thailand) Co.,Ltd.
Telephone : (66)21-45852466 Fax : (66)21-45852467
- INDONESIA** PT. Takisawa Indonesia
Telephone : (62)21-45852466 Fax : (62)21-45852467
- INDIA** SAP Takisawa Machine Tools Private Ltd.
Telephone : (91)80-26662386 Fax : (91)80-26662392
- CHINA** Takisawa (Shanghai) Co., Ltd.
Telephone : (86)21-6235-0938 Fax : (86)21-6235-0905
- USA** Takisawa, Inc.
Telephone : (1)847-419-0046 Fax : (1)847-419-0043
- GERMANY** Takisawa Machine Tool Germany Representative Office
Telephone : (49)2056-2598-15 Fax : (49)2056-5994-79